

Performed:

## DECLARATION OF PERFORMANCE № 0613.00



System 2+

(1)Product: HD Clay masonry units

(2)Type: ANDALUSIA WHITE

Manufacturing number: see labeling

(3) Intended use(s): In masonry walls, columns and partitions for unprotected masonry

(4)Manufacturer: CERÁMICA MALPESA S.A. Autovía A-4 km 303, 23710 Bailén (JAÉN) ESPAÑA

(5)Assesment and verification of constancy of performance:
(6) Notified body: AENOR 0099

- Initial inspection of the manufacturing plant and of factory production control.

- Continuous survaillance, assesment and evaluation of factory production control and

issued certificate number.

Document-date of issue: COMPLIANCE CERTIFICATE OF FACTORY PRODUCTION CONTROL

Nº 0099/CPR/A73/0021 de 25/11/2005

(7)		DECLARED PER	FORMANCE				
ESSENTIAL FEATURES		PERFORMANCES			HARMONISED TECHNICAL SPECIFICATIONS		
Dimensions		Туре					
		Regular	Plaquette	Lintel	Special		
		215*102*65	215*102*65 215*80*65 215*60*65	215*102*65	NPD		
Tolerances	category	T2			NPD		
Range	category	R2		NPD			
Configuration		Group	2	Group 4	NPD	]	
Compressive strength (perpendicular to bedface)		≥ 40 N/mm²	NPD			EN 771-1:2011	
Class		1	NPD				
Moisture movement		≤ 0.55 mm/m					
Bond strength		0.15 N/mm <sup>2</sup>					
Active soluble salts content		Class S2					
Reaction to fire		Euroclass A1					
Water absorption		≤ 6%					
Water vapour permeability		50/100					
Gross dry density		1500 kg/m³ ± 10% NPD			1		
Thermal properties		0.69 W/mK NPD					
Durability		Class F2					
Dangerous substances		NPD					

- . The performance of the product identified in points 1 and 2 are in accordance with the declared performance in point 7.
- This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of the manufacturer:

Place and date of issue:

Bailén, 14 de noviembre de 2016

José Malpesa Guerrero

CEO