

## DECLARATION OF PERFORMANCE № 0604.01



System 2+

(1)Product: HD Clay masonry units

(2)Type: CATAL ONLA

CATALONIA LIGHT GREY
Manufacturing number: see labeling

(3)Intended use(s): In masonry walls, columns and partitions for unprotected masonry

(4) Manufacturer: CERÁMICA MALPESA S.A. Autovía A-4 km 303, 23710 Bailén (JAÉN) ESPAÑA

(5) Assesment and verification of constancy of performance:

(6) Notified body: AENOR 0099

Performed: - Initial inspection of the manufacturing plant and of factory production control.

- Continuous survaillance, assesment and evaluation of factory production control and

issued certificate number.

Document-date of issue: COMPLIANCE CERTIFICATE OF FACTORY PRODUCTION CONTROL

Nº 0099/CPR/A73/0021 de 25/11/2005

(7)		DECLARED PERI	FORMANCE			
ESSENTIAL FEATURES		PERFORMANCES				HARMONISED TECHNICAL SPECIFICATIONS
Dimensions		Туре				
		Regular	Plaquette	Lintel	Special	
		215*102*65	215*102*65 215*80*65 215*60*65	215*102*65	NPD	
Tolerances	category	T2			NPD	
Range	category	R2			NPD	
Configuration		Group	Group 2 Group 4 NPD		EN 771-1:2011	
Compressive strength (perpendicular to bedface)		≥ 40 N/mm <sup>2</sup>	2 NPD			
Class		I	NPD			
Moisture movement		≤ 0.50 mm/m				
Bond strength		0.15 N/mm <sup>2</sup>				
Active soluble salts content		Class S2				
Reaction to fire		Euroclass A1				
Water absorption		≤ 6%				
Water vapour permeability		50/100				
Gross dry density		1500 kg/m <sup>3</sup> ± 10% NPD				
Thermal properties		0.69 W/mK	0.69 W/mK NPD			]
Durability		Class F2				
Dangerous substances		NPD				

- The performance of the product identified in points 1 and 2 are in accordance with the declared performance in point 7.
- This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.
- Signed on behalf of the manufacturer:

Place and date of issue:

Bailén, April, 28th 2017

José Malpesa Guerrero

CEO