ASSESSMENT GUIDELINE FOR MASONRY BRICK NEN-EN 771-1

	Bezoekadres : Gelmswijk 4 - 9665 RR – Oude Pekela Postadres : Postbus 28 - 9665 ZG – Oude Pekela Telefoon : 0597-613 920 Website : www.strating.nl	SKG-IKOB Certificatie

CERTIFICATE NUMBER IKB 1046/12

PRODUCT GROUP	UNPROTECTED, CATEGORY I, GROUP 1, FIRE BEHAVIOR A1 STRONG PRESS **BRITISH**				
PRODUCT TYPE	**STANDARD FORMAT** PERFORATED DOLLARD BSF				
PRODUCT TYPE					
PRODUCT CODE	BSF-PW-0083-12				
VISUAL FEATURES	UNSANDED		STRUCTURE		SUBMISSION DATE
ON VISIBILITY	SAND		GLAZE		
	SLIPPERY		ENGOBE		
DIMENSIONS	Length: **215** mm Width: **102** mm Height: **65** mm				ORDER
TOLERANCE CATEGORY	T1	T2			
	Divergent:				
SIZE SPREADS	R1	R2			NUMBER
CATEGORY	Divergent:				
INITIAL	Very little suction			(<0.5)	
WATER SUCTION	Mating suction			(0.5 - 1.5)	DELIVERY DATE
kg / (m².min)	Normally suction			(1.5 - 4.0)	
	Highly absorbent			(> 4.0)	
WATER INTAKE	Voluntary water absorption (mass%):		≤ 10%		WORK
	Voluntary water absorption (mass%):		≤ 9%		
	Voluntary water absorption (mass%): Gross		≤ 7%		
VOLUMIC MASS (kg / m3)	density (bvm):			1566 kg / m3	
TOLERANCE CATEGORY					
VOLUMINOUS MASS	D1	D2	20%		ARCHITECT
CHEMICAL	WATER SOLUBLE SODIUM, POTASSIUM			S0	
PROPERTIES	ENMAGNESIUM			S1	
				S2	CONTRACTOR
FROST - THAW	F0				
RESISTANCE	F2, FROST CLASS C, BRL 1007 F2,				
	FROST CLASS D, BRL 1007				CLIENT
HEAT CONDUCTIVITY λ	0.56 W / Mk				
WATER VAPOR TRANSMISSION µ	50/100				
SHAPED	YES				
BUILDING DECISION	NO				
SPECIFIC	Precision masonry / curvature according to BRL 1007				
APPLICATIONS	Product for painting (SO4 ≤ 0.10%)				
AVERAGE	5.0	7.5	10.0	12.5	
PRESSURE STRENGTH	15.0	20.0	25.0	30.0	
(N / mm2)	35.0	40.0	45.0	...	
ADDITIONAL	This specification concerns a select sample from				APPLICANT
INFORMATION FROM	said sorting.				
PRODUCER	The dimensions are taken from the last production				
	batch.				INITIALS
	Production may still need to be carried out for this				
	project.				
	The roughness of the stone can influence the size.				

IKOBKB
KOMO
Q BRL 1007

CHECK BOXES WITH GRAY ASCENSION OR OUTLINE FAT LINES IF APPLICABLE