Advies KNB 26juni2013

Declaration of Performance (DoP)

DoP nr. 2013-E-KM 099

KM 099 Wimbledon Red Mixture

HD units for use in unprotected (protected) masonry walls, colums and partitions

Steenfabriek Klinkers B.V.; Brusselseweg 700, 6219 NP, Maastricht, The Netherlands

2.	Type number:	

Product-type:

3. Intended uses:

1.

- Name and contact adress of the manufacturer: 4.
- 6. System of assessment and verification of constancy of performance: 7. The Notified Body:

2+ IKOB BKB

Notified Body BCCA N° NB 0749 performed under system 2+ the initial inspection of the manufacturing plant and of the factory production control, performed the continuous surveillance, assessment and evaluation of the factory production control and issued the certificate of conformity of the factory production control.

8. 9. Declared performance:

HD Masonry brick ((Category I, ac	cording to	5 EN 7	71-1:2011)	
Essential charateristics	Perfo	Performance			Harmonized technical specification
Length		215		mm	
Width		100		mm	
Height		65		mm	
Dimensional tolerances (I / w / h)	T1	± 6/4	/3	mm	
Range (I / w / h)	Rm	14/10	/6	mm	
Flatness of bed faces		NPD			
Parallelism of bed faces		NPD			
Gross dry density		1550		kg/m³	
Net dry density	W	WNG WDF		kg/m³	
Density tolerance: Class / %	D1	± 10)	%	
Volume of frogs		NPD		%	
Group Eurocode		1			
Mean compressive strenght perpendicular to bed faces		15		N/mm□	
Normalized compressive strenght perpendicular to bed faces		15		N/mm□	
Compressive strenght not perpendicular to bed faces		NPD		N/mm	
Bond strength		NPD		N/mm□	
Thermal conductivity λ10,dry,unit		0.45		W/m.K	EN 1745:2012
Water vapour permeability		50/100			EN 1745:2012
Durability angainst freeze/thaw: freeze/thaw resistance		F2			
Free water absorption		20		%	
Initial rate of water absorption:		1,0 - 5,0		kg/m□.mi	n
Active soluble salts content		S2			
Dimensional stability : moisture movement		NPD		mm/m	
Dangerous substances	(Complies			NL-BBk
Reaction to fire		NPD			

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by: I. Brabant Function

Place and date of issue Signature

General manager Maastricht, 28-6-2013

Haling