Declaration of Performances (DoP)				
DoP-Nr.: 2017-SK-KM655				S B.V.
Declaration of Performances				
	Steenfabriek Klinkers BV			
Product-type:	Brusselseweg 700			
WDF Harston Blend	+ -	19 NP Maast		
Type number: KM 655		The Netherlaı	nas	
Add code to dimensions	ŝ			
	1			
Intended use of the construction product, in accordance with the relevant harmonized technical specification, as determined by the manufacturer:	NEN EN 771-1			
HD products for use in unprotected masonry walls and columns.				
System for assessment and verification of constancy of performance of the construction product.		2+		
The notified body IKOBKB 0957, preformed under system 2+ the the initial inspection of the manufacturing plant and the factory production control, performed the continuous surveillance, assessment and evaluation of the factory production control and issued the certificate of conformity of the factory.		Ceccrificee SKC-IR Certificate 0957-CPR-11	ίΟΒ	
Appearance:				
Hand form brick with frog				
Declaration of Performances		EN 771-1		
Length x Width x Height	215x10	0x65	mm	
Dimensional tolerances (I/w/h)	T1 <u>+</u>	6/4/3	mm	
Range (I/w/h)	R1	9/6/4	mm	
Flatness of bed faces		NPD		
Parallelism of bed faces		NPD		
Gross dry density		1375	kg/m³	
Net dry density		NPD	kg/m³	
Density tolerance: Class / %	D1 <u>+</u>	10	%	
Volume of frogs Group Euro code		NPD 2	%	
compressive strength * perpendicular to bed faces			N/mm²	
* Mean compressive strength perpendicular to bed faces * Normalized compressive strength perpendicular to bed faces	+	10 15	N/mm ²	
Compressive strength not perpendicular to bed faces	+	NPD	,	
Bond strength	1	NPD	N/mm ²	
Thermal conductivity λ10,dry, unit		0,36	W/m.K	EN 1745
Water vapor permeability	1	5/100		EN 1745
Durability against freeze/thaw: freeze/thaw resistance		F2		
Free water absorption		20	%	
Initial rate of water absorption		1,0 - 5,0	kg/m².min	
Active soluble salts content		S2		
Dimensional stability : moisture movement		NPD	mm/m	
Dangerous substances		Complies		NL-BBK
Reaction to fire This declaration of performance is issued under the exclusive responsibility of the manufacturer. Signed for and on behalf of the manufacturer by:	I. Brabant (Gen	NPD eral Manager)	
Place and date of issue	Maastricht (NL),	6-7-2017		