Advies KNB 26juni2013

Declaration of Performance (DoP)

DoP nr. 2013-E-KM 7093-2

KM 7093-2 Imperial London Stock Product-type:

Type number: 2.

3. Intended uses: HD units for use in unprotected (protected) masonry walls, colums and partitions

Name and contact adress of the manufacturer: Steenfabriek Klinkers B.V.; Brusselseweg 700, 6219 NP, Maastricht, The Netherlands

System of assessment and verification of constancy of performance:

The Notified Body: IKOB BKB

Notified Body BCCA N° NB 0749 performed under system 2+ the initial inspection of the manufacturing plant and of the factory production control, performed the continuous surveillance, assessment and evaluation of the factory production control and issued the certificate of conformity of the factory

8. production control.

Declared performance:

HD Masonry brick (Category I, according to EN 771-1:2011)					
Essential charateristics	Perfo	rma	ince		Harmonized technical specification
Length	225			mm	
Width	115		mm		
Height		70		mm	
Dimensional tolerances (I / w / h)	T1	±	7/5/4	mm	
Range (I / w / h)	Rm	14	/10/6	mm	
Flatness of bed faces	NPD				
Parallelism of bed faces	NPD				
Gross dry density	1550			kg/m³	
Net dry density	WNG WDF			kg/m³	
Density tolerance: Class / %	D1	±	10	%	
Volume of frogs		NPD		%	
Group Eurocode		1			
Mean compressive strenght perpendicular to bed faces		15		N/mm□	
Normalized compressive strenght perpendicular to bed faces		15		N/mm□	
Compressive strenght not perpendicular to bed faces		NI	PD	N/mm□	
Bond strength		NPD		N/mm□	
Thermal conductivity λ10,dry,unit		0.45		W/m.K	EN 1745:2012
Water vapour permeability	50/100		100		EN 1745:2012
Durability angainst freeze/thaw: freeze/thaw resistance		F2			
Free water absorption	20		%		
Initial rate of water absorption:	1,0 - 5,0		kg/m□.min		
Active soluble salts content	S2				
Dimensional stability : moisture movement		NPD		mm/m	
Dangerous substances	С	Complies			NL-BBk
Reaction to fire		NPD			

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

I. Brabant Function General manager

Place and date of issue Signature

Maastricht, 28-6-2013