Declaration of Performances (DoP)	STEENFABRIEK KLINKERS
DoP-Nr.: 2025-\$K-KM051-pink	Sinds 1938
Declaration of Performances	Steanfahriak Klinkara BV
Product-type:	Steenfabriek Klinkers BV  Brusselseweg 700
WDF zilverzand zalmkleurig (pink)	Brasselseweg 700
Type number:	6219 NP Maastricht
KM 051-pink  Add code to dimensions	The Netherlands
Intended use of the construction product, in accordance with the relevant harmonized technical specification, as determined by the manufacturer:	NEN EN 771-1
HD products for use in unprotected masonry walls and columns.	
System for assessment and verification of constancy of performance of the construction product.	2+
The notified body IKOBKB 0957, preformed under system 2+ the the initial inspection of the manufacturing plant and the factory production control, performed the continuous surveillance, assessment and evaluation of the factory production control and issued the certificate of conformity of the factory.	Gecertificeerd door SKG-IKOB Certificatie 0957-CPR-1104
Appearance:	
Full hand form brick	-11
Declaration of Performances	EN 771-1
Length x Width x Height	214x100x65 mm
Dimensional tolerances (I/w/h)  Range (I/w/h)	T1 <u>+</u> 6/4/3 mm R1 9/6/4 mm
Flatness of bed faces	NPD
Parallelism of bed faces	NPD
Gross dry density	1375 kg/m³
Net dry density	NPD kg/m³
Density tolerance: Class / %	D1 <u>+</u> 10 %
Volume of frogs	NPD %
Group Euro code	2
compressive strength * perpendicular to bed faces  * Mean compressive strength perpendicular to bed faces	15 N/mm²
* Normalized compressive strength perpendicular to bed faces	20 N/mm²
Compressive strength not perpendicular to bed faces	NPD
Bond strength	NPD N/mm²
Thermal conductivity λ10,dry, unit	0,36 W/m.K EN 1745
Water vapor permeability	5/100 EN 1745
Durability against freeze/thaw: freeze/thaw resistance	F2
Free water absorption	16 %
Initial rate of water absorption  Active soluble salts content	1,0 - 5,0 kg/m².min
Dimensional stability : moisture movement	NPD mm/m
Dangerous substances	Complies NL-BBK
Reaction to fire	NPD
This declaration of performance is issued under the exclusive responsibility of the manufacturer.  Signed for and on behalf of the manufacturer by:	I. Brabant (General Manager)
Place and date of issue	Maastricht (NL), 16-10-2025